

Platform Model: Acer Aspire L3600, CPU: Intel®Core™2 Duo E6750, RAM: 1GB DDR II, Chip Set: Intel® G33 ICH9-DH HDBENCH: V3.40(100MB), XP Professional SP3, WinSAT: Win7, Controller: IT1167,MPTool version: 1.67.10.0																
Flash Part Num.	CE#	Flash Type	BUS Width	HDBench Single				HDBench Dual				ATTO Single		ATTO Dual		Note.
				Seq. Read	Seq. Write	Random R	Random W	Seq. Read	Seq. Write	Random R	Random W	Seq. Read	Seq. Write	Seq. Read	Seq. Write	
Samsung																
K9ABG08U0A	1	TLC	8 bit	9,282	4,325	10,158	977	14,691	6,993	16,020	1,156	9,854	4,552	13,030	8,305	
K9BCG08U1A	2	TLC	8 bit	n/a	n/a	n/a	n/a	14,465	7,008	15,526	1,158	n/a	n/a	13,557	8,046	
K9GAG08U0D	1	MLC	8 bit	18,882	4,972	18,354	1,663	n/a	n/a	n/a	n/a	19,358	7,404	n/a	n/a	
K9GAG08U0E	1	MLC	8 bit	12,924	5,306	12,824	1,512	22,135	8,110	22,135	3,221	13,030	5,765	21,931	10,046	
K9GBG08U0M	1	MLC	8 bit	15,982	9,216	15,942	4,047	26,855	14,091	26,743	2,903	16,368	17,325	24,732	25,165	
K9LCG08U1M	2	MLC	8 bit	15,942	10,191	16,060	2,186	25,593	13,737	24,914	3,146	16,288	18,207	25,960	24,552	
K9HDG08U5M	4	MLC	8 bit	15,454	10,112	15,417	2,212	26,743	13,238	26,961	3,053	15,790	17,236	25,960	24,139	
K9PFG08U5M	4	MLC	8 bit	15,945	10,551	16,020	2,258	25,498	14,562	25,689	3,038	16,368	17,660	25,811	25,516	
Hynix																
H27UBG8T2ATR	1	MLC	8 bit	20,225	8,703	20,345	1,825	30,055	12,481	30,188	2,540	20,585	11,432	30,504	16,833	
H27UCG8U5ATR	2	MLC	8 bit	19,616	9,899	19,737	2,025	31,811	13,291	31,950	2,473	20,670	13,865	30,504	16,288	
H27UDG8V5ATR	2	MLC	8 bit	20,410	10,759	20,475	2,037	30,055	15,027	29,115	2,853	20,798	13,612	30,093	20,295	
Intel																
29F64G08AAME1	1	MLC	8 bit	19,445	9,989	19,441	1,321	26,743	12,457	26,310	2,056	20,336	11,222	28,556	15,643	
Toshiba																
TC58NVG4D2FTA00	1	MLC	8 bit	19,273	10,207	19,158	2,554	29,124	12,272	28,240	2,686	18,921	11,278	28,496	16,975	
TC58NVG5D2FTAI0	1	MLC	8 bit	17,615	8,878	17,519	2,751	24,538	14,759	24,633	2,162	17,325	10,308	24,916	17,385	
TC58NVG4T2ETA00	1	TLC	8 bit	22,669	5,242	22,362	846	29,510	11,030	28,739	2,448	20,798	8,409	28,197	12,782	
TC58NVG5T2ETA00	1	TLC	8 bit	21,342	6,659	21,205	1,808	29,915	9,899	29,115	2,002	22,774	10,535	27,224	10,535	